




Rockfon® Multiflex™ Opal Baffles

FEATURES & BENEFITS

- Vertically-installed baffles
- Two-sided galvanized frame
- High sound absorption contributes to acoustic comfort
- Fast and easy to install
- Ideally-suited for acoustical corrections

APPLICATIONS

- Cafe/Restaurants
- Museum
- Cellular Office
- Open Plan Office
- Light Industry



LEED® V4 HIGHLIGHTS

Materials and Resources (MR)

- Construction & Demolition Waste Management Planning ✓
- Interiors Life Cycle Impact Reduction - Designed for Flexibility ✓
- Building Product Disclosure and Optimization - Environmental Product Declarations ✓
- Building Product Disclosure and Optimization - Sourcing of Raw Materials ✓
- Building Product Disclosure and Optimization - Material Ingredients ✓
- Construction and Demolition Waste Management ✓

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- Interior Lighting ✓
- Acoustic Performance ✓

RECYCLED CONTENT: UP TO 42%

Rockfon® Multiflex™ Opal Baffles



Edge designation	Item number	Modular size (nominal)	lbs/unit	units/carton	Fire Class	Light Reflectance	Sag resistance (relative humidity)	LOW VOC
	3201	12" x 48" x 2"	3.75	12	A	0.64	UP TO 100%	✓
	3226	18" x 48" x 2"	5.51	6	A	0.64	UP TO 100%	✓
	3251	24" x 48" x 2"	7.28	6	A	0.64	UP TO 100%	✓

MATERIAL

Stone wool (Mineral Wool) framed baffle with factory painted glass scrim on both sides

ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



FIRE PERFORMANCE:

Surface burning characteristics:

UL723 (ASTM E84) Flame Spread Index: 0
 Smoke Developed Index (UL Labeled): 5
 CAN/ULC S102 Flame Spread Index: 5
 Smoke Developed Index: 0



VOC/FORMALDEHYDE EMISSIONS

All Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



WARRANTY INFORMATION:

30-Year Limited Product Warranty.
 See www.rockfon.com



HYGIENE

Stone wool provides no sustenance to microorganisms



CLEANING

- Vacuum



ACOUSTICAL PROPERTIES

		Sabins per baffle					
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
Tested in ISO Type J mounting: 3 x 15'9" rows, 2'9" centers	12" x 48" x 2"	1.9	3.9	4.5	6.0	6.1	6.0
Tested in ISO Type J mounting: 3 x 15'9" rows, 2'9" centers	18" x 48" x 2"	3.5	4.9	6.6	8.1	8.2	8.3
Tested in ISO Type J mounting: 3 x 15'9" rows, 2'9" centers	24" x 48" x 2"	3.7	4.7	7.7	9.0	9.5	9.3